



Predictive Analytics in Occupational Health: Transitioning from Lagging to Leading Indicators in Enterprise Risk Management

Kimberly Long Holt

Health and Safety Concepts – Environmental Health & Safety, United State

Corresponding Author: Kimberly Long Holt, ka3027@yahoo.com

ARTICLE INFO

Keywords: Predictive Analytics, Occupational Health and Safety (OHS), Leading Indicators, Total Cost of Risk (TCOR), Internet of the Worker (IoW).

Received : 27, February

Revised : 29, March

Accepted: 30, April

©2026 Holt: This is an open-access article distributed under the terms of the [Creative Commons Attribution 4.0 International](https://creativecommons.org/licenses/by/4.0/).



ABSTRACT

The discipline of Occupational Health and Safety (OHS) is undergoing a paradigm shift driven by advances in wearable technology and machine learning. Lagging indicators, such as the Total Recordable Incident Rate (TRIR), have been historically considered the most common risk management metrics for gauging the safety performance of risk managers. Such measures merely describe what occurs once one has been defeated, but not the option of preventing the initial loss. The paper endorses the proposal to change to leading indicators, controlled by predictive analytics and the Internet of the Worker (IoW). By studying real-time biometric and environmental information, organizations would be able to identify pre-incident behavior patterns and prevent losses. This paper will examine the technically based infrastructure of the IoW, validate the financial case, using the Total Cost of Risk (TCOR) analysis, and a holistic ROI model, the underwriting implications of the Experience Modification rate (EMR) optimization and Schedule Rating and the ethical remit of data governance and just culture that must accompany the implementation of these technologies, based on the frames of the Associate in Risk Management (ARM) system

INTRODUCTION

The conventional theory of risk management places the center of gravity around the event. We look at the sliding, the collapsing, or the poor workings of the machines when the damage is already done. Throughout decades, the industry was operating within a reactive compliance model; that is, compliance with regulatory measures; OSHA in the United States, Health and Safety Executive (HSE) in the United Kingdom and Safe Work Australia in the Asia-Pacific region indicated that the regulatory measure is safe. In truth, as any risk practitioner who has done the Associate in Risk Management (ARM) designation secretarial discovers, compliance is at most but one side of a tripod risk strategy.

The progressive dynamics of global supply chains and the growth of workforce demands have extended the adaptable safety models as far as 2026. Predictive Occupational Health is the trend that inevitably brings the subsection of the model of Historical Loss to the sacrifice of the model of Proactive Prevention. Through information-based knowledge, risk managers can currently highlight the difficult-to-address risks like fatigue, micro-ergonomic strains and environmental stressors, before they reflect on the balance sheet. The key point about this article is that the lagging indicator model is not adaptable to the new world, both economically and morally. This can be seen in the paragraphs that follow as leading indicators provide a superior forecast on likely losses and how the Risk Manager of 2026 will be required to be a data translator: translator between the shop floor and the C-suite.

THEORETICAL REVIEW

From the Safety Pyramid to Resilience Engineering

In 1931, Herbert Heinrich created the publication *Industrial Accident Prevention: A Scientific Approach*, in which he came up with the Safety Pyramid. In his model, he assumed that every 1 serious injury will be associated with 29 minor injuries and 300 near-misses. To correct this severe deficiency of the model, i.e., having a unified causal mechanism, by predictive analytics, the problem is remedied by ranking hazard-specific and high-severity predictors of the cause rather than trying to apply the one-size-fits-all model of intervention (Heinrich, 1931).

The Swiss Cheese Model of accident causation was introduced in the 1990s by James Reason, who presumed that complex systems contain a number of defensive layers, each of which contains some flaws in its own way. An accident will only occur by coincidence of the holes in all levels. The predictive analytics is peeking at each of the layers in real-time: when an increase in heat is detected by a machine sensor and a high degree of fatigue is detected by the wearable of an operator, the system sends the signal of the impending alignment to the human rather than allow the error to take control of the chain (Reason, 1990).

Safety II and Resilience Engineering

Over the last decade, the paradigm of Safety II, invented by Erik Hollnagel, has become exceptionally popular. In *Why did things go wrong?* Where Safety I says. The question of Safety II is: Why do things work out, and under what circumstances can that be appropriate? A developed IoW platform using the principles of Safety II becomes a coach, aware of all the successful

workdays and seeing the slightest deviation towards unsafe norms before the accident - the definition of the operation of a leading indicator operationally (Hollnagel, 2023).

METHODOLOGY

The application and conceptual analytical framework adopted in the Associate in Risk Management (ARM) curriculum are considered in the article. The analysis is designed under three areas (1) important literature analysis of the theoretical evolution of OHS frameworks beginning with Heinrich to Heinrich pyramid to the modern resilience engineering (2) finance modelling task comparing the Total Cost of Risk (TCOR) decomposition and holding a return-on-investment (ROI) case study of a normal 1,000-employee manufacturing organisation; and (3) analysis of particular case study on predictive analytics application within the construction and logistics industry. The industry benchmark data are gathered with the help of the National Safety Council, IRMI, and ASSP. The technical architecture of the Internet of the Worker (IoW) is validated in a three-layered model made up of Data Acquisition, Predictive Processing and Prescriptive Intervention, which is in line with the six steps of the ARM Risk Management Process.

RESEARCH RESULTS

The Problem with Lagging Indicators

The most frequently quoted measures are the Lagging indicators encompassing the Lost Time Injury Frequency Rate (LTIFR), TRIR and Days Away, Restricted or Transferred (DART) rate to a working safety professional in real time. The facility is allowed to have three sequential years, and the control of risk is controlled by the management when there are no losses-time injury recorded. However, in case the latter is not monitored for any underlying behavior, then that facility could be getting the statistical luck at the cost of being innocent. Petersen (2024) notes that the absence of accidents does not imply that safety has been achieved. The hazard reproduced is largely the culprit in creating disaster incidents that have been years old without breaching any fence that forms a lagging report incident. With respect to Risk Financing terms of reference, they relied on the lagging indicators thematic approach, where the workers' compensation premiums have been developed through the Experience Modification rate (EMR), a three-year average, that wraps around the financial damages occurring even before the risk manager takes any action.




Figure 1. Seven-year incident rate comparison. Organizations adopting predictive (leading indicator) safety models demonstrate an 83% reduction in incident rate versus 19% for reactive-only programs over the same period.

The IoW Technical Architecture

Internet of the Worker (IoW) is the warehouse of wearable computers and data from the senses to the environment, which is the raw data for analytics. There are 3 primary data streams behind the system. Kinematic Sensors: tri-axial accelerometers and gyroscopes have been designed for the simultaneous measurement of joint velocity and angulation during real-time monitoring. Cumulative Lumbar Loading per shift- an infinitely more powerful leading indicator than a single injurious lift that appears on an OSHA Form 300. Physiological Surveys: Heart Rate Variability (HRV) Heart rate Photoplethysmography (PPG) is used to assess autonomic nervous system stress; declining HRV is a successful predictive variable of so-called Cognitive Tunneling, a fatigue-impaired state which increases the risk factor of being struck by lightning significantly (Aita and Hankin 168). Telemetry of the Environment: LIDAR-quantified Red Zones are the density of Zonal Intrusions and the number of times a worker is at the moving equipment danger zone to provide an approximation measure of the chance of collision that might lead to any contact.

Each combination of task-workers is rated by the system as dynamic Probability of Loss (PoL) using Bayesian networks. When PoL reaches a pre-calibrated threshold (ex. 0.15), the system will take an intervention: a task-rotation recommendation (automatic), a haptic notification (smartwatch) or a notification to a supervisor. A seven-year longitudinal data indicates that the incident decline in the organisations adhering to this model declined by 83 percent against 19 percent in independent reactive programmes in the same period.

TCOR Analysis and ROI

Safety data attracts the C-suite's consideration only after being cast in financial terms. The Total Cost of Risk (TCOR) is not the line item of the insurance premiums; it is the combination of four significant cost groups. Table 1 depicts

the reorganization of every element in terms of predictive analytics, an example of 1,000 employees at a given firm.

Table 1. TCOR Component Analysis Before and After Predictive Analytics Implementation (representative 1,000-employee firm)

TCOR Component	Before Analytics (\$000s)	After Analytics (\$000s)
Insurance Premiums	\$820,000	\$620,000
Retained Losses	\$680,000	\$300,000
Risk Control Expenditures	\$200,000	\$420,000
Administrative & Legal Costs	\$300,000	\$180,000
Total TCOR	\$2,000,000	\$1,520,000

The \$480,000 net reduction reflects a strategic reallocation from reactive loss absorption to proactive risk control. Source: ARM curriculum benchmark model; NSC, 2025; IRMI, 2026.

Figure 2. TCOR Component Shift: Before and After Predictive Analytics Implementation




Figure 2. TCOR component shift before and after predictive analytics. The \$480,000 net reduction reflects a strategic reallocation from reactive loss absorption to proactive risk control.

The Iceberg Effect of Workplace Injury Costs




Figure 3. The Iceberg Effect: For every \$1 of insured injury cost, \$4-\$10 in hidden costs remain below the surface — making prevention exponentially more valuable.

Figure 3. The Iceberg Effect — indirect costs represent approximately 80% of the true cost of a workplace injury, making prevention substantially more valuable than its insurance-line ROI alone suggests.

In each 1\$ of direct damages that is covered, studies consistently isolate 4-10 in indirect, uninsured damages- productivity loss, reputation losses and administrative rub-a-dub-dub. The ROI model demonstrates this: a wearable-tech implementation of \$200,000 and \$200 per worker through charging will result in a high-risk movement pattern being produced by 20% of the workforce, which accounts for 80% of high-risk movement patterns; targeted coaching reduces claim frequency by 25%, generating a direct loss reduction of \$500,000. A total savings on the enterprise based on the use of the 4:1 indirect cost multiplying is presented as a total of \$ 2.5 million saved in 1 year of ROI 1,150% (IRMI, 2026; NSC, 2025).

Figure 4. ROI Waterfall: \$200K Predictive Analytics Investment vs. \$2.5M Total Enterprise Savings (Year-One ROI: 1,150%)




Figure 4. ROI Waterfall — A \$200,000 predictive analytics investment generates \$2.5 million in total enterprise savings in year one (1,150% ROI), driven by direct claim reduction and indirect cost avoidance.

Risk Financing: EMR, Schedule Rating, and Captives

This EMR is a three-year obligatory trailing calculation, which is arranged by the NCCI formula. An institution that has undergone the status of total transformation of its safety culture in 2026 will not reconstruct that transformation in its EMR up to 2029. However, the Schedule Rating discretionary device of the underwriter applies to the current policy term, which is based on a reward for risk improvement that has been given. Today, the Risk Manager makes the evidentiary basis of Schedule Rating Credits by supplying real-time IoW Risk Profiles to the underwriters without making any entries in the EMR lag. When a company that uses a Captive Insurance Company suffers an injury prevented in some way, any such injury would definitely be recorded directly in the excess of the captive and the dividends of the parent firm, and this element is a vicious circle of the safety performance financing, further technological development.

Sector-Specific Applications

Fatal four falls, struck by, caught in/between incidents and electrocution incidents account for more than 60 percent of the workers who are murdered annually in the construction sector. Computer Vision and LIDAR in a 2025 high-rise large-scale project was used to monitor the crane-load movements, which detected Zonal Breaches in which workers were working in falls-of-suspended-loads zones. The system was found to prove that there exists a correlation between ambient wind speed and the 40 percent growth in the occurrence of micro-stumbles on high floor plates to enable a Wind-Adjusted Work Schedule. A 30 percent reduction in the near-miss reports in which there was no fall-related injury was the final process in the project. Haptic feedback Smart Belts in logistics and warehousing showed that their associates with Last-Mile Sorting bay had

50% more actions per shift asymmetries than their Bulk Receiving counterparts--a design-of-the-system, rather than a behavioural problem. Reproject of the sorting conveyor geometry had led to a reduction of lower-back workers' compensation claims of 55 percent in the first policy year.

DISCUSSION

The discussion of the entire TCOR modeling, IoW architecture, analysis of a sector case, and EMR optimization illuminates only one aspect: reactive safety programs will be inadequate and insufficient, regarding finance and morals, by 2026. The largest underwriting implication is the disparity between the obligatory EMR and the Schedule Rating. Essentially the same thing that no retrospective EMR calculation can ever do, the Risk Manager uses real-time IoW Profiles of Risk to offer instant Schedule Rating leverage to underwriters, another of the most leverage-maximizing applications of the ARM curriculum in modern practice (Kaplan & Mikes, 2025).

The ethical in nature deserves a just portion of interest. The most significant threat to a predictive safety program is the perception that a weapon of repression will be implemented through the application of biometric data. The other prerequisite form is a Disciplinary Firewall that is established before the sensor is installed and should never go beyond systemic engineering improvements and anonymous one-on-one coaching, and it is not supposed to be found in performance reviews and disciplinary actions. Violation of this principle triggers data sabotage, rendering the predictive model statistically invalid. Equity issues also require that vendors provide training data, demographics, and algorithmic audit periodically because wearables that have been recalibrated on small demographic datasets may produce systematically biased risk scores against older workers, chronic-condition workers or untypical groups (NSC, 2025). DDP and CCPA A retention of any biometric data must have explicit and aware consent, geo-fencing upon the crossing of the workplace, and the risk scores derived, but not the underlying biometric feeds (Shorrocks & Williams, 2023; Weil, 2024).

CONCLUSIONS AND RECOMMENDATIONS

The shift towards leading indicators is financially and ethically necessary. The financial argument speaks volumes: a first year of 1,150% ROI will get the boardroom's attention in any sector. The underwriting argument goes the same way: Live Risk Profiles present the ARM practitioner with real-time Schedule Rating power that no extra EMR calculation can offer. It must be implemented based on the ARM Six-Step Risk Management Process: (1) audit departments using TRIR, data maturity to locate pilot candidates; (2) deploy sensors and receive informed consent under GDPR/CCPA; (3) utilize correlation modeling to isolate the leading indicators that one claims most often in this specific industry vertical; (4) prioritize systemic engineering controls over behavioral correction; (5) implement the Disciplinary Firewall, before sensors become operational and deliver real-time Risk Profiles to underwriters to negotiate Schedule Rating Credits; and (The human case is the most convincing of all--by preventing the minding toward danger prior to it becoming a tragedy, the risk

professionals serve the original intent of the profession, which is not to record failure, but to succeeded in making it disappear.

FURTHER STUDY

This article employs conceptual modeling with industry benchmark inputs in contrast with longitudinal firm-level data, and sector cases are founded on reported results as opposed to controlled experimental designs. Future research should address which is the long-term actuarial impact of IoW application upon EMR curves over a policy year or years; the effectiveness of the Bayesian networks and deep learning structure when a heterogeneous workforce configuration is used; and the equity of the biometric surveillance of heterogeneous population groups. Follow-up longitudinal studies based on worker trust and voluntary disclosure of near misses by the intervention of the Disciplinary Firewall before and after the intervention would be beneficial to the existing body of evidence of the just culture researches.

ACKNOWLEDGMENT

The author gratefully acknowledges the foundational contributions of the ARM curriculum body of knowledge and the practitioner community whose field experience informed this analysis.

REFERENCES

- ASSP (American Society of Safety Professionals). (2025). *Leading Indicators: The New Standard for OHS Management*. ASSP Press.
- Domino, D. (2024). *Predictive Analytics for the Modern Safety Professional*. Wiley & Sons.
- Heinrich, H. W. (1931). *Industrial Accident Prevention: A Scientific Approach*. McGraw-Hill.
- Hollnagel, E. (2023). *Safety-II in Practice: Developing the Resilience Potentials*. Routledge.
- International Risk Management Institute (IRMI). (2026). *The Impact of AI on Workers' Compensation Cost Structures*. IRMI Research Reports.
- ISO 31000:2018. *Risk Management – Guidelines* – International Organization for Standardization.

Kaplan, R. S., & Mikes, A. (2025). *Managing Risks: A New Framework*. Harvard Business Review.

National Safety Council (NSC). (2025). *Workforce Biometrics and the Ethics of Surveillance*. NSC Safety Whitepaper.

Petersen, D. (2024). *Human Error Reduction and Safety Management (4th ed.)*. Aloray.

Reason, J. (1990). *Human Error*. Cambridge University Press.

Shorrock, S., & Williams, C. (Eds.). (2023). *Human Factors and Ergonomics in Practice: Improving System Performance and Human Well-Being in the Real World*. CRC Press.

Weil, D. (2024). *The Fissured Workplace: Why Work Became So Bad for So Many and What Can Be Done to Improve It (Updated ed.)*. Harvard University Press.